



Αποκλειστικά  
για Ψύξη

# MFH MAUI ΦΟΡΗΤΗ ΜΟΝΑΔΑ



A<sup>+</sup>

## Χαρακτηριστικά

Compact κατασκευή με  
καθαρές σχεδιαστικές  
γραμμές  
Οικονομικό και αποδοτικό  
(MFH 10:3.10/A+)

## Λειτουργίες

ΠΟΙΟΤΗΤΑ / ΚΑΘΑΡΟΤΗΤΑ ΑΕΡΑ



AIR FILTER



AUTO  
CLEAN DRY

ΛΕΙΤΟΥΡΓΙΕΣ ΧΡΗΣΤΗ



I FEEL



NIGHT MODE



24 H

PROGRAMMABLE  
TIMES



RESTART  
(MEMORY)



REMOTE CONTROL  
LOCK

ΛΕΙΤΟΥΡΓΙΕΣ ΕΓΚΑΤΑΣΤΑΣΗΣ



SELF DIAGNOSTIC

Φιλικό προς το περιβάλλον με Gas R290  
Εύκολη μετακίνηση μέσω τροχών και χειρολαβής  
Εύκολο στην χρήση μέσω ψηφιακής οθόνης και  
ασύρματου control  
Υψηλή άνεση και αίσθηση δροσιάς χάρις στην απόδοση  
λειτουργίας του

## MFH MAUI

Indoor unit		AW-MFH010-C41	AW-MFH012-C41
Phase		Single phase	Single phase
<b>COOLING</b>			
Rated power	kW	<b>2.93</b>	<b>3.52</b>
Rated power input	kW	0.945	1.357
Current	A	4.5	5.9
EER/Energy label		<b>3,10/A+</b>	2,60/A
Operating limits	°C	17°/35° Dry bulb	
<b>INDOOR UNIT</b>			
Type		Monobloc	Monobloc
Sound pressure level to 1 m (LS/MS/HS)	dB(A)	50/51/52	50/51/52
Sound power level	dB(A)	56	63
Airflow (LS/MS/HS)	m <sup>3</sup> /h	355/370/420	355/370/420
Diameter flexible emission duct	mm	150	
Length range of heat emission duct	m	0.50 - 1.5	
Dehumidification	l/h	1.6	1.8
Outline dimensions (WxHxD)	mm	467x765x397	467x765x397
Package dimensions (WxHxD)	mm	515x890x440	515x890x440
Net weight/Gross weight	kg	31.8/35.7	33/36.5
Part number		<b>7MB021060</b>	<b>7MB021061</b>
<b>POWER SUPPLY</b>			
Phase/Voltage/Frequency		1P/230V/50Hz	1P/230V/50Hz
<b>PIPE LINE</b>			
Refrigerant/GWP		<b>R290/20</b>	<b>R290/20</b>
Charge	kg	0.21	0.22