

Fan motor	Output	Rated	W	130	130	230	230	300	300	300
	Speed	Steps		3	3	3	3	3	3	3
	Model			Brushless DC motor	Brushless DC motor	Brushless DC motor	Brushless DC motor	Brushless DC motor	Brushless DC motor	Brushless DC motor
	Quantity			1	1	1	1	1	1	1
	Poles			10	10	10	10	10	10	10
Packing	Weight	kg		2.5	2.5	3	3	3	3	3
Heat exchanger	Fin	Type		Cross fin coil (Multi slit fins with hydrophilic treatment and Ø5Hi-XA tubes)	Cross fin coil (Multi slit fins with hydrophilic treatment and Ø5Hi-XA tubes)	Cross fin coil (Multi slit fins with hydrophilic treatment and Ø5Hi-XA tubes)	Cross fin coil (Multi slit fins with hydrophilic treatment and Ø5Hi-XA tubes)	Cross fin coil (Multi slit fins with hydrophilic treatment and Ø5Hi-XA tubes)	Cross fin coil (Multi slit fins with hydrophilic treatment and Ø5Hi-XA tubes)	Cross fin coil (Multi slit fins with hydrophilic treatment and Ø5Hi-XA tubes)
Piping connections	Liquid	OD	mm	6.35	6.35	6.35	9.52	9.52	9.52	9.52
			Type	Flare connection	Flare connection	Flare connection	Flare connection	Flare connection	Flare connection	Flare connection
	Gas	OD	mm	9.52	12.7	12.7	15.9	15.9	15.9	15.9
			Type	Flare connection	Flare connection	Flare connection	Flare connection	Flare connection	Flare connection	Flare connection
	Drain			VP20 (I.D. 20/O.D. 26)	VP20 (I.D. 20/O.D. 26)	VP20 (I.D. 20/O.D. 26)	VP20 (I.D. 20/O.D. 26)	VP20 (I.D. 20/O.D. 26)	VP20 (I.D. 20/O.D. 26)	VP20 (I.D. 20/O.D. 26)
	Heat insulation			Foamed polystyrene/polyethylene	Foamed polystyrene/polyethylene	Foamed polystyrene/polyethylene	Foamed polystyrene/polyethylene	Foamed polystyrene/polyethylene	Foamed polystyrene/polyethylene	Foamed polystyrene/polyethylene
	Sound absorbing insulation			Butyl Rubber	Butyl Rubber	Butyl Rubber	Butyl Rubber	Butyl Rubber	Butyl Rubber	Butyl Rubber
Power input	Cooling	Nom.	kW	3.4	5.0	5.7	6.8	9.5	12.0	13.4
	Heating	Nom.	kW	4.0	5.5	7.0	7.5	10.8	13.5	15.5
Sound power level	Cooling		dBA	60	60	56	56	58	62	62
Air filter	Type			Resin net with mold resistance	Resin net with mold resistance	Resin net with mold resistance	Resin net with mold resistance	Resin net with mold resistance	Resin net with mold resistance	Resin net with mold resistance
Dimensions	Packed unit	Width	mm	900	900	1,200	1,200	1,600	1,600	1,600
		Height	mm	890	890	890	890	890	890	890
		Depth	mm	295	295	295	295	295	295	295
	Unit	Width	mm	700	700	1,000	1,000	1,400	1,400	1,400
		Depth	mm	800	800	800	800	800	800	800
		Height	mm	245	245	245	245	245	245	245
Casing	Colour			Not painted (galvanised)	Not painted (galvanised)	Not painted (galvanised)	Not painted (galvanised)	Not painted (galvanised)	Not painted (galvanised)	Not painted (galvanised)
	Material			Galvanised steel plate	Galvanised steel plate	Galvanised steel plate	Galvanised steel plate	Galvanised steel plate	Galvanised steel plate	Galvanised steel plate
Weight	Packed unit		kg	30.5	30.5	38	38	49	49	49
	Unit		kg	28	28	35	35	46	46	46
Fan	External static pressure	High	Pa	150	150	150	150	150	150	150
		Nom.	Pa	30	30	30	30	40	50	50

[illegible]